




"A leading worldwide supplier of high efficiency filters for a variety of industries and applications."

1,500 PSIG STAINLESS STEEL HOUSINGS

The 130 and 140 series of filters are ideal for use with gaseous and liquid sample process analyzers, as well as other demanding applications. The small internal volume, compact design, and positive O-ring sealing mechanism make them perfect for challenging applications. They are constructed entirely of 316L stainless steel and are free of welds to comply with NACE MR-01-75.

For applications with higher flows and larger ports, please review our Model 150/160 series listed at the bottom of this bulletin.

These housings are also available with a PTFE seal, which requires a modified sealing design: simply add an "S" to the housing code, e.g. 132S. PTFE seals cannot be retrofitted into standard housings originally having a Viton O-ring. A high temperature gasket can only be fitted into the S version housing.



Features:

- 316L Stainless Steel Construction
- Pressure To 1,500 PSIG, Temperature To 900°F
- 3-Port Housings For Coalescing Or Bypass Filtration
- High Pressure Models Available
- Available In Hastelloy, Monel, Etc.

Applications:

- CNG Filtration
- Food And Dairy Process
- Sample Process Analyzers
- High Pressure Gas Production

At the heart of our filter products is the filter element. Choosing the correct element insures proper results for your specific application:

Disposable Microfiber Elements

Disposable Microfiber Elements are most commonly used since they offer exceptional filtration, high flows with minimal pressure drops, and excellent chemical compatibility. These are ideal for use in sample conditioning, instrumentation, CNG, and Emission/Environmental service.

- For **Coalescing (liquid removal)** and particle collection use our grade "C". We recommend starting with the 70C which is rated at 95% efficient at 0.01 micron which provides outstanding filtration, at high flow rates.
- For **Particle removal** only use grade "K". We recommend starting with the 70K which is rated at 95% efficient at 0.01 micron which provides outstanding filtration, at high flow rates.
- For **Particulate removal** above 300°F (150°C) use grade "S".



Stainless Steel 5-Layer Mesh Elements

Stainless steel elements (SS) are designed for the filtration of heavily contaminated gas samples, CNG, and liquid streams since they are recleanable by back flushing or ultrasonic cleaning. Standard microns available: 0.5, 1, 3, 10, 25, 50, 100, and 200.



Sintered PTFE


Sintered PTFE elements are used where only pure PTFE may contact the sample. They should be used in our PTFE series of housings based on the stainless steel models. Model 122P, 122PG, 130P, 130PG, 132P, 132PG, 142P. Standard microns available: 3, 10, and 25.

Sintered Polyethylene (PEL)

Sintered polyethylene elements (PEL) are used only in non-corrosive applications to remove bulk contaminants. Standard micron sizes available: 10, 25, and 75.

1,500 PSIG STAINLESS STEEL HOUSINGS

- NACE Compliant MR-01-75
- Fuel Gas Filter
- Wellhead Control Panel Filter
- Accepts Microfiber, Stainless Steel, PTFE, & PEL Filter Elements
- NPT, SAE, & Socket Weld Are Available



TECHNICAL INFORMATION

Housing Model	130	132	140	142
Housing Model w/o Drain	134	136	144	146
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1500	1500	1500	1500
Internal Volume (cc)	110	110	265	265
Maximum Temp. -Buna-N (250°F)	BN130	BN130	BN130	BN130
Maximum Temp. -EPDM (300°F)	GE130	GE130	GE130	GE130
Maximum Temp. -Viton (400°F) Standard	GV130	GV130	GV130	GV130
Maximum Temp. -Silicone (450°F)	GS130	GS130	GS130	GS130
Maximum Temp. -Kalrez (600°F)	KZ130	KZ130	KZ130	KZ130
Weight of Housing (lbs)	2.5	2.5	3.5	3.5
Principle Dimensions: (inches)				
Center Of Port To Head	0.59	0.59	0.59	0.59
Head Diameter	2.36	2.36	2.36	2.36
Overall Length	4.80	4.80	9.29	9.29
Element Removal Clearance	2.95	2.95	7.40	7.40
Filter Element Codes: (1)				
Disposable Element	25-64-□	25-64-□	25-178-□	25-178-□
Stainless Steel Element	SS-25-64-□	SS-25-64-□	SS-25-178-□	SS-25-178-□
PEL Element	PEL-25-64-□	PEL-25-64-□	PEL-25-178-□	PEL-25-178-□
PTFE Element	PT-25-64-□	PT-25-64-□	PT-25-178-□	PT-25-178-□
Materials Of Construction: (2)				
Head & Internals	316LSS	316LSS	316LSS	316LSS
Bowl	316LSS	316LSS	316LSS	316LSS
O-Rings (Standard)	Viton	Viton	Viton	Viton
Accessories:				
Mounting Bracket	MBSS130	MBSS130	MBSS130	MBSS130
Support Core	SC130	SC130	SC140	SC140
Housing Model w/ PTFE Seals	130S	132S	140S	142S
Maximum Temp. -PTFE (400°F) Standard	GP130S	GP130S	GP130S	GP130S

FLOW RATE IN SCFM FOR ABOVE ASSEMBLIES WITH GRADE 50C ⁽³⁾ or 70C ⁽⁴⁾

Air Line Pressure (PSIG)	130 Series		140 Series	
	50C	70C	50C	70C
15	6	11	10	13
30	8	16	15	19
60	13	26	25	32
100	21	44	40	50
150	29	58	55	68
250	45	89	83	106
500	87	173	163	209
1500	282	524	488	627

- Notes: (1) Replace '□' with grade required, e.g. 25-64-50C, PT-25-178-03
 (2) Material abbreviations, 316LSS = 316L Stainless Steel
 (3) Flow rates for Grade 50C rated at 99.99% against 0.01 micron
 (4) Flow rates for Grade 70C rated at 95% against 0.01 micron

1,500 PSIG STAINLESS STEEL HOUSINGS

Our Gas and Liquid Process Filters protect equipment from sample impurities by removing solids and liquids from gases up to 99.999% efficiency at 0.01 micron. This series of filters is also ideal to use in liquid sample process applications by simply employing our pleated liquid elements, or stainless steel elements. A 1 micron efficiency can be reached in liquids with the aforementioned elements.

To satisfy the extreme wide range of requirements for process sample filters, we supply a complete line of filter elements in stainless steel, polypropylene, and other corrosion-resistant materials. A choice of high efficiency borosilicate microfiber filter elements, which are inert to most liquids and gases, are also offered.

Our 150 and 160 series of high-pressure 316L stainless steel filter housings offer exceptional value and performance. The threaded head to bowl connection with captured o-ring provides positive sealing even in very corrosive and demanding applications. The 1500 PSIG rating covers the majority of gas and liquid applications.



Features:

- Filters Gases & Liquids
- 316L Stainless Steel
- 1,500 PSIG / 400°F - Standard
- 6,000 PSIG & Flanges Available
- 3-Port Housings For Coalescing
- Particulate Or Bypass Filtration

Applications:

- CNG Filtration
- Blow Molding Equipment
- Gas Production
- Food And Dairy Processing
- High Pressure Liquid Filters

At the heart of our filter products is the filter element. Choosing the correct element insures proper results for your specific application:

Disposable Microfiber Elements

Disposable Microfiber Elements are most commonly used since they offer exceptional filtration, high flows with minimal pressure drops, and excellent chemical compatibility. These are ideal for use in sample conditioning, instrumentation, CNG, and Emission/Environmental service.

- For **Coalescing (liquid removal)** and particle collection use our grade "CS". We recommend starting with the 70CS which is rated at 95% efficient at 0.01 micron which provides outstanding filtration, at high flow rates.
- For **Particle removal** only use grade "K". We recommend starting with the 70K which is rated at 95% efficient at 0.01 micron which provides outstanding filtration, at high flow rates.
- For **Particulate removal** above 300°F (150°C) use grade "S".



Stainless Steel 5-Layer Mesh Elements

Stainless steel elements (SS) are designed for the filtration of heavily contaminated gas samples, CNG, and liquid streams since they are recleanable by back flushing or ultrasonic cleaning. Standard microns available: 0.5, 1, 3, 10, 25, 50, 100, and 200.



Sintered PTFE

Sintered PTFE elements are used where only pure PTFE may contact the sample. They should be used in our PTFE series of housings based on the stainless steel models. Model 122P, 122PG, 130P, 130PG, 132P, 132PG, 142P. Standard microns available: 3, 10, and 25.

Sintered Polyethylene (PEL)

Sintered polyethylene elements (PEL) are used only in non-corrosive applications to remove bulk contaminants. Standard micron sizes available: 10, 25, and 75.

1,500 PSIG STAINLESS STEEL HOUSINGS

- Ideal Compressed Natural Gas Filter
- NACE Complaint MR-01-75 For Sour Service
- Mechanical Seal Filter
- Seal Gas Filtration
- Accepts Microfiber, Stainless Steel, PTFE, & PEL Filter Elements



TECHNICAL INFORMATION

Housing Model	150*	151	152
Port Size (NPT)	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1500	1500	1500
Internal Volume (cc)	1500	1500	1500
Maximum Temp. -Buna-N (250°F)	BN150	BN150	BN150
Maximum Temp. -EPDM (300°F)	GE150	GE150	GE150
Maximum Temp. -Viton (400°F) Standard	GV150	GV150	GV150
Maximum Temp. -Silicone (450°F)	GS150	GS150	GS150
Maximum Temp. -Kalrez (600°F)	KZ150	KZ150	KZ150
Weight of Housing (lbs)	22.0	22.0	22.0
Principle Dimensions: (inches)			
Center Of Port To Head	1.18	1.85	1.85
Head Diameter	4.33	4.33	4.52
Overall Length	14.75	15.58	15.58
Element Removal Clearance	9.05	9.05	9.05
Filter Element Codes: (1)			
Disposable Element	51-230-□	51-230-□	51-230-□
Stainless Steel Element	SS-51-230-□	SS-51-230-□	SS-51-230-□
PEL Element	PEL-51-230-□	PEL-51-230-□	PEL-51-230-□
PTFE Element	PT-51-230-□	PT-51-230-□	PT-51-230-□
Materials Of Construction: (2)			
Head & Internals	316LSS	316LSS	316LSS
Bowl	316LSS	316LSS	316LSS
O-Rings (Standard)	Viton	Viton	Viton
Accessories:			
Mounting Bracket	MB150	MB150	MB150
Support Core	SC150	SC150	SC150

FLOW RATE IN SCFM FOR ABOVE ASSEMBLIES WITH GRADE 50C ⁽³⁾ or 70C ⁽⁴⁾

Air Line Pressure (PSIG)	150 Series	
	50C	70C
15	38	79
30	56	116
60	93	198
100	151	314
150	209	430
250	319	667
500	650	1334
1500	1897	3944

- Notes: (1) Replace '□' with grade required, e.g. 51-230-50CS, PT-51-230-03
 (2) Material abbreviations, 316LSS = 316L Stainless Steel
 (3) Flow rates for Grade 50C rated at 99.99% against 0.01 micron
 (4) Flow rates for Grade 70C rated at 95% against 0.01 micron
 (*) Also available in 3/4" port

1,500 PSIG STAINLESS STEEL HOUSINGS

TECHNICAL INFORMATION

Housing Model	160*	161	162
Port Size (NPT)	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1500	1500	1500
Internal Volume (cc)	2700	2700	2700
Maximum Temp. -Buna-N (250°F)	BN160/2	BN160/2	BN160/2
Maximum Temp. -EPDM (300°F)	GE160/2	GE160/2	GE160/2
Maximum Temp. -Viton (400°F) Standard	GV160/2	GV160/2	GV160/2
Maximum Temp. -Silicone (450°F)	GS160/2	GS160/2	GS160/2
Maximum Temp. -Kalrez (600°F)	KZ160/2	KZ160/2	KZ160/2
Weight of Housing (lbs)	38.0	38.0	38.0
Principle Dimensions: (inches)			
Center Of Port To Head	1.18	1.85	1.85
Head Diameter	4.33	4.33	4.52
Overall Length	24.72	25.12	25.12
Element Removal Clearance	17.87	17.87	17.87
Filter Element Codes: (1)			
Disposable Element	51-476-□	51-476-□	51-476-□
Stainless Steel Element	SS-51-476-□	SS-51-476-□	SS-51-476-□
PEL Element	PEL-51-476-□	PEL-51-476-□	PEL-51-476-□
PTFE Element	PT-51-476-□	PT-51-476-□	PT-51-476-□
Materials Of Construction: (2)			
Head & Internals	316LSS	316LSS	316LSS
Bowl	316LSS	316LSS	316LSS
O-Rings (Standard)	Viton	Viton	Viton
Accessories:			
Mounting Bracket	MB150	MB150	MB150
Support Core	SC160	SC160	SC160

FLOW RATE IN SCFM FOR ABOVE ASSEMBLIES WITH GRADE 50C ⁽³⁾ or 70C ⁽⁴⁾

Air Line Pressure (PSIG)	160 Series	
	50C	70C
15	64	87
30	125	143
60	160	221
100	256	354
150	354	488
250	546	754
500	1091	1508
1500	3248	4466

- Notes: (1) Replace '□' with grade required, e.g. 51-476-50CS, PT-51-476-03
 (2) Material abbreviations, 316LSS = 316L Stainless Steel
 (3) Flow rates for Grade 50C rated at 99.99% against 0.01 micron
 (4) Flow rates for Grade 70C rated at 95% against 0.01 micron
 (*) Also available in 3/4" ports

Our wide range of filter element materials and micron sizes allow multiple uses for these housings:

Gas Service Applications:

Coalescing and/or Particulate
 CNG Filtration
 Blow Molding Equipment
 Food Plant Caustic Service
 High Pressure Compressor Service
 General High Pressure Air Service
 Adsorption Cartridges; Carbon, Silica Gel, 13X, etc.
 Pleated for High Dirt Holding Capacity

Liquid Service Applications:

Particulate
 High Flow Sample Service
 Fuel Filtration
 Solvents / Coolants
 Cryogenic Service
 Corrosive Environmental Service
 Lubricants
 C.I.P. Service (Clean In Place)