



Technical Data

- PTFE Construction
- 1/2" NPT / 1/4" NPT Sample Port
- 100 PSIG Maximum Pressure
- Internal Volume (with Element): 215cc
- Viton O-Ring (Standard-Included)
- Total Weight: 6 lbs.
- Flow Rate: See Fast Loop Product Bullentin Page

Elements Available:

SS-25-178-xxT	Stainless Steel Filter Element Comes Standard with Teflon Seals "T" Micron Sizes: 005, 01, 03, 10, 25, 50, 100 and 200
PT-25-178-xx	PTFE Filter Element Micron Sizes: 03 and 25
PEL-25-178-xx	PEL (Polyethylene) Filter Element Micron Sizes: 10, 25, and 75

Replace "xxx" with grade or micron needed. See [Filter Element Guide](#) for more information.

Available O-Rings:

GV136IL-3	Viton (-15°F to 400°F) **Standard - Included**
BN136IL-3	Buna-N (-40°F to 250°F)
KZ136IL-3	Perfluoroelastomer (5°F to 600°F)
GS136IL-3	Silicone (-65°F to 400°F)
GE136IL-3	EPDM (-65°F to 300°F)

For the Latest Drawing Details

Please Call 586-802-5561

Or

Email jennifer@unitedfiltration.com

Replacement Parts:

GV136IL-3

Viton (-15°F to 400°F) (A) **Standard - Included******

EC146IL-3

Stainless Steel End Cap (B)

