



Technical Data

- 316L Stainless Steel Construction
- 1" NPT / 1/2" NPT Sample Port
- 150 PSIG Maximum Pressure
- Internal Volume (with Element): 430cc
- Viton O-Ring (Standard-Included)
- Total Weight: 9 lbs.
- Flow Rate: See Fast Loop Product Bulletin Page

Elements Available:

SS-51-230-xxT

Stainless Steel Filter Element

Comes Standard with Teflon Seals "T"
Micron Sizes: 005, 01, 03, 10, 25, 50, 100 and 200

Replace "xx" with grade or micron needed. See [Filter Element Guide](#) for more information.

Available O-Rings:

GV150IL-3

Viton (-15°F to 400°F) ****Standard - Included****

BN150IL-3

Buna-N (-40°F to 250°F)

KZ150IL-3

Perfluoroelastomer (5°F to 600°F)

GS150IL-3

Silicone (-65°F to 400°F)

GE150IL-3

EPDM (-65°F to 300°F)

For the Latest Drawing Details

Please Call 586-802-5561

Or

Email jennifer@unitedfiltration.com

Replacement Parts:

GV150IL-3

Viton (-15°F to 400°F) (A) **Standard - Included******

EC150IL-3

Stainless Steel End Cap (B)

