



# Coalescing Filter Regulators

## PRODUCT FEATURES / BENEFITS

- ◆ Compact Design
- ◆ Integral Piggy-Back Regulator
- ◆ Clear Nowl for at a Glance Monitoring Available
- ◆ Regulator Ranges Available: 0-30, 5-60, & 10-130
- ◆ Sight Glass Optional on Metal Bowl (SG)
- ◆ Self - Relieving
- ◆ Point-Of-Use Regulation of Air Systems
- ◆ Valve Protection
- ◆ Instrument Air Line Control
- ◆ I/P Control Valve Protection
- ◆ Air Control Cabinet

Experience clean, dry compressed air and consistent pressure control in one smart, space-saving solution. Our coalescing filter regulators combine high-efficiency filtration with a reliable self-relieving regulator to protect your equipment and keep your system running at its best. The vertical piggy-back design reduces installation footprint, while the top-mounted bayonet knob makes pressure adjustments quick, simple, and intuitive—so you get premium air quality and performance with less hassle.



Housing Model	FR516	FRA516
Port Size (NPT)	1/8" or 1/4"	1/8" or 1/4"
Gauge Ports (NPT)	1/8"	1/8"
Maximum Pressure (psig)	150	250
Weight of Housing (lbs)	1.0	1.0
Principle Dimensions: (inches)		
Head Diameter	1.50	1.50
Overall Length	5.77	5.77
Maximum Temp. (120°F) Standard Buna-N Diaphragm & O-Ring	BNFR516	BNFR516
Filter Element Codes: Coalescing Element (Standard - Included) <b>*Other Elements Available-View Drawing*</b>	12-32-50C	12-32-50C
Regulator Range: 0-30, 5-60, & 10-130 PSIG	30R, 60R, 130R	30R, 60R, 130R
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>FR516</u></b>	<b><u>FRA516</u></b>

Housing Model	FRT066	FRAT066	FRT076	FRAT076
Port Size (NPT)	1/4" or 1/2"	1/4" or 1/2"	1/2"	1/2"
Gauge Ports (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	150	250	150	250
Weight of Housing (lbs)	2.0	3.0	3.0	4.0
Principle Dimensions: (inches)				
Head Diameter	2.50	2.50	2.50	2.50
Overall Length	10.13	10.13	14.00	14.00
Maximum Temp. (120°F) Standard Buna-N Diaphragm & O-Ring	BNFR066	BNFR066	BNFR066	BNFR066
Filter Element Codes: Coalescing Element (Standard - Included) <b>*Other Elements Available-View Drawing*</b>	25-64-50CW	25-64-50CW	25-178-50C	25-178-50C
Regulator Range Available 0-30, 5-60, & 10-130 PSIG	30R, 60R, 130R	30R, 60R, 130R	30R, 60R, 130R	30R, 60R, 130R
<b>Drawing</b> **For More Detail & Options**	<b><u>FRT066</u></b>	<b><u>FRAT066</u></b>	<b><u>FRT076</u></b>	<b><u>FRAT076</u></b>

Housing Model w/ Automatic Drain	FRFT066	FRAFT066	FRFT076	FRAFT076
Port Size (NPT)	1/4" or 1/2"	1/4" or 1/2"	1/2"	1/2"
Gauge Ports (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	150	250	150	250
Weight of Housing (lbs)	2.0	3.0	3.0	4.0
Principle Dimensions: (inches)				
Head Diameter	2.50	2.50	2.50	2.50
Overall Length	10.13	10.13	14.00	14.00
Maximum Temp. (120°F) Standard Buna-N Diaphragm & O-Ring	BNFR066	BNFR066	BNFR066	BNFR066
Filter Element Codes: Coalescing Element (Standard - Included) <b>*Other Elements Available-View Drawing*</b>	25-64-50CW	25-64-50CW	25-127-50C	25-127-50C
Regulator Range: 0-30, 5-60, & 10-130 PSIG	30R, 60R, 130R	30R, 60R, 130R	30R, 60R, 130R	30R, 60R, 130R
<b>Drawing</b> **For More Detail & Options**	<b><u>FRFT066</u></b>	<b><u>FRAFT066</u></b>	<b><u>FRFT076</u></b>	<b><u>FRAFT076</u></b>