

Housing Model	LP360A	LP365A	LP370A	LP375A
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/8"	1/8"	1/8"	1/8"
Maximum Pressure (psig)	500	500	500	500
Internal Volume (cc)	163	163	310	310
Weight of Housing (lbs)	1.5	1.5	1.5	1.5
Principle Dimensions: (inches)				
Center Of Port To Head (A)	0.61	0.61	0.61	0.61
Head Diameter (B)	2.72	2.72	2.72	2.72
Overall Length (C)	6.26	6.26	10.32	10.32
Element Removal Clearance (D)	3.07	3.07	7.21	7.21
Maximum Temp. (-40°F to 250°F) Standard Buna-N O-Ring <b>Other Elastomers Available Upon Request</b>	BN360	BN360	BN360	BN360
Filter Element Codes: <b>Stainless Steel Element with Snap-On Teflon Seals (Standard-Sold Separate) (1)</b>	<b>SS-25-64-25T</b>	<b>SS-25-64-25T</b>	<b>SS-25-178-25T</b>	<b>SS-25-178-25T</b>
For Critical Applications – Stainless Steel Element with Snap-On Teflon Seals	SS-25-64-03T	SS-25-64-03T	SS-25-178-03T	SS-25-178-03T
Coalescing Element - If Liquids are Present	25-64-70CS	25-64-70CS	25-178-70CS	25-178-70CS
Flow Rate @ 100 PSIG Air (SCFM)	44	44	129	129
Maximum Recommended Liquid (Water) Flow Rate With 3 Micron Stainless Steel Element (GPM)	4	4	7	7

Notes: (1) Our Stainless Steel Elements come complete with Snap-On Teflon Seals – Elements are Sold Separately

<b>Housing Model</b>	<b>LP380AHP</b>	<b>LP383AHP</b>	<b>LP385AHP</b>	<b>LP390AHP</b>
Port Size (NPT)	3/4"	1"	1 1/2" or 2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1,200	1,200	1000	1000
Internal Volume (cc)	760	760	1500	2950
Weight of Housing (lbs)	8	8	11	14
Principle Dimensions: (inches)				
Center Of Port To Head (A)	1.34	1.34	1.58	1.58
Head Diameter (B)	4.33	4.33	5.51	5.51
Overall Length (C)	12.09	12.09	15.67	25.39
Element Removal Clearance (D)	6.19	6.19	9.30	18.98
Maximum Temp. (-40°F to 250°F) Standard Buna-N O-Ring <b>Other Elastomers Available Upon Request</b>	BN380	BN380	BN385	BN385
Filter Element Codes: <b>Stainless Steel Element with Snap-On Teflon Seals (Standard-Sold Separate) (1)</b>	<b>SS-38-152-25T</b>	<b>SS-38-152-25T</b>	<b>SS-51-230-25T</b>	<b>SS-51-476-25T</b>
For Critical Applications – Stainless Steel Element with Snap-On Teflon Seals	SS-38-152-03T	SS-38-152-03T	SS-51-230-03T	SS-51-476-03T
Coalescing Element - If Liquids are Present	38-152-70CS-DOE	38-152-70CS-DOE	51-230-70CS	51-476-70CS
Flow Rate @ 100 PSIG Air (SCFM)	361	361	630	990
Maximum Recommended Liquid (Water) Flow Rate With 3 Micron Stainless Steel Element (GPM)	10	10	19	40

Notes: (1) Our Stainless Steel Elements come complete with Snap-On Teflon Seals – Elements are Sold Separately