



# Sight Glass Housings

## PRODUCT FEATURES / BENEFITS

- ◆ Pyrex Bowl with Safety Guard
- ◆ Service is Quick and Simple with Only One Removable Base
- ◆ Level Indicator
- ◆ Flow Indicator
- ◆ Four Standard Sizes
- ◆ No Tools Required to Service

Four standard sizes are available, based on our Pyrex and stainless steel filter assembly design. Each housing incorporates a guarded Pyrex bowl for visual monitoring of tank or boiler liquid levels. The compact Model SG117 is specifically designed for flow observation applications.

All models feature a double open-ended glass bowl clamped between two stainless steel end plates. This construction eliminates the need for external through-bolts, providing a simplified assembly for ease of installation and service.



Housing Model	SG117	SG127	SG137	SG147
Port Size (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	100	100	100	100
Internal Volume (cc)	26	36	105	255
Principle Dimensions: (inches)				
Head Diameter	1.57	1.57	2.20	2.20
Overall Length	3.07	3.82	4.65	9.13
Removal Clearance	2.46	2.76	3.54	8.03
Maximum Temp. (400°F) Standard Viton O-Ring	GVSG117	GVSG127	GVSG137	GVSG137
<b>Drawing</b> **For More Detail & Options**	<b>SG117</b>	<b>SG127</b>	<b><u>SG137</u></b>	<b>SG147</b>