

| Housing Model | FR516 | FRA516 |
|---|---------------------|----------------------|
| Port Size (NPT) | 1/8" or 1/4" | 1/8" or 1/4" |
| Gauge Ports (NPT) | 1/8" | 1/8" |
| Maximum Pressure (psig) | 150 | 250 |
| Weight of Housing (lbs) | 1.0 | 1.0 |
| Principle Dimensions: (inches) | | |
| Head Diameter | 1.50 | 1.50 |
| Overall Length | 5.77 | 5.77 |
| Maximum Temp. (120°F) Standard Buna-N Diaphragm & O-Ring | BNFR516 | BNFR516 |
| Filter Element Codes: Coalescing Element (Standard - Included) *Other Elements Available-View Drawing* | 12-32-50C | 12-32-50C |
| Regulator Range: 0-30, 5-60, & 10-130 PSIG | 30R, 60R, 130R | 30R, 60R, 130R |
| Drawing **For More Detail & Options** | <u>FR516</u> | <u>FRA516</u> |

| Housing Model | FRT066 | FRAT066 | FRT076 | FRAT076 |
|---|----------------------|-----------------------|----------------------|-----------------------|
| Port Size (NPT) | 1/4" or 1/2" | 1/4" or 1/2" | 1/2" | 1/2" |
| Gauge Ports (NPT) | 1/4" | 1/4" | 1/4" | 1/4" |
| Maximum Pressure (psig) | 150 | 250 | 150 | 250 |
| Weight of Housing (lbs) | 2.0 | 3.0 | 3.0 | 4.0 |
| Principle Dimensions: (inches) | | | | |
| Head Diameter | 2.50 | 2.50 | 2.50 | 2.50 |
| Overall Length | 10.13 | 10.13 | 14.00 | 14.00 |
| Maximum Temp. (120°F) Standard Buna-N Diaphragm & O-Ring | BNFR066 | BNFR066 | BNFR066 | BNFR066 |
| Filter Element Codes: Coalescing Element (Standard - Included) *Other Elements Available-View Drawing* | 25-64-50CW | 25-64-50CW | 25-178-50C | 25-178-50C |
| Regulator Range Available 0-30, 5-60, & 10-130 PSIG | 30R, 60R, 130R | 30R, 60R, 130R | 30R, 60R, 130R | 30R, 60R, 130R |
| Drawing **For More Detail & Options** | <u>FRT066</u> | <u>FRAT066</u> | <u>FRT076</u> | <u>FRAT076</u> |

| Housing Model w/ Automatic Drain | FRFT066 | FRAFT066 | FRFT076 | FRAFT076 |
|---|-----------------------|------------------------|-----------------------|------------------------|
| Port Size (NPT) | 1/4" or 1/2" | 1/4" or 1/2" | 1/2" | 1/2" |
| Gauge Ports (NPT) | 1/4" | 1/4" | 1/4" | 1/4" |
| Maximum Pressure (psig) | 150 | 250 | 150 | 250 |
| Weight of Housing (lbs) | 2.0 | 3.0 | 3.0 | 4.0 |
| Principle Dimensions: (inches) | | | | |
| Head Diameter | 2.50 | 2.50 | 2.50 | 2.50 |
| Overall Length | 10.13 | 10.13 | 14.00 | 14.00 |
| Maximum Temp. (120°F) Standard Buna-N Diaphragm & O-Ring | BNFR066 | BNFR066 | BNFR066 | BNFR066 |
| Filter Element Codes: Coalescing Element (Standard - Included) *Other Elements Available-View Drawing* | 25-64-50CW | 25-64-50CW | 25-127-50C | 25-127-50C |
| Regulator Range: 0-30, 5-60, & 10-130 PSIG | 30R, 60R, 130R | 30R, 60R, 130R | 30R, 60R, 130R | 30R, 60R, 130R |
| Drawing **For More Detail & Options** | <u>FRFT066</u> | <u>FRAFT066</u> | <u>FRFT076</u> | <u>FRAFT076</u> |