

| Housing Model | 385AHP | 385AHPF | 390AHP | 390AHPF |
|--|--------------------------------------|---------------------------------------|--------------------------------------|---------------------------------------|
| Port Size (NPT) | 1 1/2" or 2" | 1 1/2" or 2" | 2" | 2" |
| Drain Type (NPT) | Petcock | Automatic | Petcock | Automatic |
| Maximum Pressure (psig) | 1,000 | 250 | 1,000 | 250 |
| Internal Volume (cc) | 1500 | 1440 | 2950 | 2890 |
| Weight of Housing (lbs) | 11 | 11 | 14 | 14 |
| Principle Dimensions: (inches) (1) | | | | |
| Center Of Port To Head | 1.58 | 1.58 | 1.58 | 1.58 |
| Head Diameter | 5.51 | 5.51 | 5.51 | 5.51 |
| Overall Length | 15.67 | 15.67 | 25.39 | 25.39 |
| Element Removal Clearance | 9.30 | 9.30 | 18.98 | 18.98 |
| Maximum Temp. (250°F) | | | | |
| Standard Buna-N O-Ring | BN385AHP | BN385AHP | BN385AHP | BN385AHP |
| Filter Element Codes: | | | | |
| Coalescing Element (Standard - Included) | 51-230-70CS | 51-230-70CS | 51-476-70CS | 51-476-70CS |
| *Other Elements Available- View Drawing | | | | |
| Drawing **For More Detail & Options** | <u>385AHP</u> | <u>385AHPF</u> | <u>390AHP</u> | <u>390AHPF</u> |
| Housing Model w/Indicator Maximum Pressure with Indicator – 300 PSIG | <u>385AHPVDI</u> | <u>385AHPFVDI</u> | <u>390AHPVDI</u> | <u>390AHPFVDI</u> |

Notes: (1) Dimensions are based on housing and does not include measurement for indicator