

<b>Housing Model</b>	<b>310A</b>	<b>315A</b>	<b>360A</b>	<b>365A</b>	<b>370A</b>	<b>375A</b>
Port Size (NPT)	1/8"	1/4"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	Petcock	Petcock	Petcock	Petcock	Petcock	Petcock
Maximum Pressure (psig)	500	500	500	500	500	500
Internal Volume (cc)	45	45	163	163	310	310
Weight of Housing (lbs)	0.5	0.5	1.5	1.5	1.5	1.5
Principle Dimensions: (inches)						
Center Of Port To Head	0.39	0.39	0.61	0.61	0.61	0.61
Head Diameter	1.57	1.57	2.72	2.72	2.72	2.72
Overall Length	4.65	4.65	6.26	6.26	10.32	10.32
Element Removal Clearance	1.50	1.50	3.07	3.07	7.21	7.21
Maximum Temp. (240°F) Standard Viton O-Ring	BN315	BN315	BN360	BN360	BN360	BN360
Filter Element Codes: Coalescing Element (Standard - Included) <b>*Other Elements Available- View Drawing</b>	12-32-70C	12-32-70C	25-64-70C	25-64-70C	25-178-70C	25-178-70C
<b>Drawing</b> **For More Detail & Options**	<b><u>310A</u></b>	<b><u>315A</u></b>	<b><u>360A</u></b>	<b><u>365A</u></b>	<b><u>370A</u></b>	<b><u>375A</u></b>

Housing Model	380AHP	383AHP	385AHP	390AHP
Port Size (NPT)	3/4"	1"	1 1/2" or 2"	2"
Drain Type (NPT)	Petcock	Petcock	Petcock	Petcock
Maximum Pressure (psig)	1,500	1,500	1,000	1,000
Internal Volume (cc)	760	760	1500	2950
Weight of Housing (lbs)	8	8	11	14
Principle Dimensions: (inches)				
Center Of Port To Head	1.34	1.34	1.58	1.58
Head Diameter	4.33	4.33	5.51	5.51
Overall Length	12.09	12.09	15.67	25.39
Element Removal Clearance	6.19	6.19	9.30	18.98
Maximum Temp. (250°F) Standard Viton O-Ring	BN380	BN380	BN385	BN385
Filter Element Codes: Coalescing Element (Standard - Included) <b>*Other Elements Available- View Drawing</b>	TRE38-152-70CS	TRE38-152-70CS	51-230-70CS	51-476-70CS
<b>Drawing</b> **For More Detail & Options**	<b><u>380AHP</u></b>	<b><u>383AHP</u></b>	<b><u>385AHP</u></b>	<b><u>390AHP</u></b>

Housing Model	110	112	114	116	120	122	124	126
Port Size (NPT)	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"
Drain Type (NPT)	1/8"	1/4"	None	None	1/8"	1/4"	None	None
Maximum Pressure (psig)	5000	5000	5000	5000	5000	5000	5000	5000
Internal Volume (cc)	25	25	25	25	34	34	34	34
Weight Of Housing (lbs)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Principle Dimensions: (inches)								
Center Of Port To Head	0.39	0.39	0.39	0.39	0.39	0.39	0.39	0.39
Head Diameter	1.42	1.42	1.42	1.42	1.42	1.42	1.42	1.42
Overall Length	2.92	2.92	2.92	2.92	3.98	3.98	3.98	3.98
Element Removal Clearance	1.57	1.57	1.57	1.57	2.36	2.36	2.36	2.36
Maximum Temp. (400°F) Standard Viton O-Ring	GV110	GV110	GV110	GV110	GV110	GV110	GV110	GV110
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	12-32-□	12-32-□	12-32-□	12-32-□	12-57-□	12-57-□	12-57-□	12-57-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>110</u></b>	<b><u>112</u></b>	<b><u>114</u></b>	<b><u>116</u></b>	<b><u>120</u></b>	<b><u>122</u></b>	<b><u>124</u></b>	<b><u>126</u></b>
<b>Housing w/ PTFE Seals</b> Maximum Temp.-PTFE (400°F) Standard	<b><u>110S</u></b>	<b><u>112S</u></b>	<b><u>114S</u></b>	<b><u>116S</u></b>	<b><u>120S</u></b>	<b><u>122S</u></b>	<b><u>124S</u></b>	<b><u>126S</u></b>

Notes: (1) Replace '□' with grade required, e.g. 12-32-50C

Housing Model	110HP	112HP	114HP	116HP	120HP	122HP	124HP	126HP
Port Size (NPT)	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"
Drain Type (NPT)	1/8"	1/4"	None	None	1/8"	1/4"	None	None
Maximum Pressure (psig) (1)	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000
Internal Volume (cc)	23	23	23	23	32	32	32	32
Weight of Housing (lbs)	5.0	5.0	5.0	5.0	6.0	6.0	6.0	6.0
Principle Dimensions: (inches)								
Center Of Port To Head	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87
Head Diameter	2.56	2.56	2.56	2.56	2.56	2.56	2.56	2.56
Overall Length	4.13	4.13	4.13	4.13	5.12	5.12	5.12	5.12
Element Removal Clearance	1.57	1.57	1.57	1.57	2.56	2.56	2.56	2.56
Maximum Temp. (400°F) Standard Viton O-Ring	GV110HP	GV110HP	GV110HP	GV110HP	GV110HP	GV110HP	GV110HP	GV110HP
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	12-32-□	12-32-□	12-32-□	12-32-□	12-57-□	12-57-□	12-57-□	12-57-□
<b>Drawing</b> **For More Detail & Options**	<b><u>110HP</u></b>	<b><u>112HP</u></b>	<b><u>114HP</u></b>	<b><u>116HP</u></b>	<b><u>120HP</u></b>	<b><u>122HP</u></b>	<b><u>124HP</u></b>	<b><u>126HP</u></b>

Notes: (1) Replace '□' with grade required, e.g. 12-32-50C

<b>Housing Model</b>	<b>122LB-PVF</b>	<b>122LB-PVF-PEL20</b>	<b>122LB-PVF-70CS</b>
Port Size (NPT)	1/4"	1/4"	1/4"
Drain Type (NPT)	1/4"	1/4"	1/4"
Maximum Pressure (psig)	5000	5000	5000
Internal Volume (cc)	58	58	58
Reservoir / Sump Volume (cc)	15	15	15
Weight on Housing (lbs)	1.5	1.5	1.5
Principle Dimensions: (inches)			
Center Of Port To Head	0.39	0.39	0.39
Head diameter	1.42	1.42	1.42
Overall Length	5.98	5.98	5.98
Element Removal Clearance	3.35	3.35	3.35
Maximum Temp. (400°F) Standard Viton O-Ring	GV110	GV110	GV110
Filter Element Codes: Polyethylene Element (Standard - Included) <b>*Other Elements Available-View Drawing</b>	No Element Included	PEL-12-76-20	12-76-70CS
<b>Drawing (Nylon Internals)</b> <b>**For More Detail &amp; Options**</b>	<b><u>122LB-PVF</u></b>	<b><u>122LB-PVF</u></b>	<b><u>122LB-PVF</u></b>

Housing Model	130	132	134	136	140	142	144	146
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/4"	1/4"	None	None	1/4"	1/4"	None	None
Maximum Pressure (psig)	1500	1500	1500	1500	1500	1500	1500	1500
Internal Volume (cc)	100	100	100	100	260	260	260	260
Weight of Housing (lbs)	2.5	2.5	2.5	2.5	3.5	3.5	3.5	3.5
Principle Dimensions: (inches)								
Center Of Port To Head	0.59	0.59	0.59	0.59	0.59	0.59	0.59	0.59
Head Diameter	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36
Overall Length	4.80	4.80	4.80	4.80	9.33	9.33	9.33	9.33
Element Removal Clearance	2.95	2.95	2.95	2.95	7.40	7.40	7.40	7.40
Maximum Temp. (400°F) Standard Viton O-Ring	GV130	GV130	GV130	GV130	GV130	GV130	GV130	GV130
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	25-64-□	25-64-□	25-64-□	25-64-□	25-178-□	25-178-□	25-178-□	25-178-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>130</u></b>	<b><u>132</u></b>	<b><u>134</u></b>	<b><u>136</u></b>	<b><u>140</u></b>	<b><u>142</u></b>	<b><u>144</u></b>	<b><u>146</u></b>
<b>Housing w/ PTFE Seals</b> Maximum Temp. -PTFE (400°F) Standard	<b><u>130S</u></b>	<b><u>132S</u></b>	<b><u>134S</u></b>	<b><u>136S</u></b>	<b><u>140S</u></b>	<b><u>142S</u></b>	<b><u>144S</u></b>	<b><u>146S</u></b>

Notes: (1) Replace '□' with grade required, e.g. 25-64-50C

Housing Model	130HP	132HP	134HP	136HP	140HP	142HP	144HP	146HP
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/4"	1/4"	None	None	1/4"	1/4"	None	None
Maximum Pressure (psig)	3000	3000	3000	3000	3000	3000	3000	3000
Internal Volume (cc)	110	110	110	110	270	270	270	270
Weight of Housing (lbs)	4.5	4.5	4.5	4.5	7.5	7.5	7.5	7.5
Principle Dimensions: (inches)								
Center Of Port To Head	0.59	0.59	0.59	0.59	0.59	0.59	0.59	0.59
Head Diameter	2.52	2.52	2.52	2.52	2.52	2.52	2.52	2.52
Overall Length	5.04	5.04	5.04	5.04	9.53	9.53	9.53	9.53
Element Removal Clearance	2.95	2.95	2.95	2.95	7.40	7.40	7.40	7.40
Maximum Temp. (400°F) Standard Viton O-Ring	GV130HP	GV130HP	GV130HP	GV130HP	GV130HP	GV130HP	GV130HP	GV130HP
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	25-64-□	25-64-□	25-64-□	25-64-□	25-178-□	25-178-□	25-178-□	25-178-□
<b>Drawing</b> **For More Detail & Options**	<b><u><a href="#">130HP</a></u></b>	<b><u><a href="#">132HP</a></u></b>	<b><u><a href="#">134HP</a></u></b>	<b><u><a href="#">136HP</a></u></b>	<b><u><a href="#">140HP</a></u></b>	<b><u><a href="#">142HP</a></u></b>	<b><u><a href="#">144HP</a></u></b>	<b><u><a href="#">146HP</a></u></b>

Notes: (1) Replace '□' with grade required, e.g. 25-64-50C

Housing Model	130VP	132VP	134VP	136VP	140VP	142VP	144VP	146VP
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/4"	1/4"	None	None	1/4"	1/4"	None	None
Maximum Pressure (psig)	6000	6000	6000	6000	6000	6000	6000	6000
Internal Volume (cc)	130	130	130	130	270	270	270	270
Weight of Housing (lbs)	10.5	10.5	10.5	10.5	15.0	15.0	15.0	15.0
Principle Dimensions: (inches)								
Center Of Port To Head	0.83	0.83	0.83	0.83	0.83	0.83	0.83	0.83
Head Diameter	3.35	3.35	3.35	3.35	3.35	3.35	3.35	3.35
Overall Length	6.44	6.44	6.44	6.44	10.92	10.92	10.92	10.92
Element Removal Clearance	2.95	2.95	2.95	2.95	7.40	7.40	7.40	7.40
Maximum Temp. (400°F) Standard Viton O-Ring	GV130VP	GV130VP	GV130VP	GV130VP	GV130VP	GV130VP	GV130VP	GV130VP
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	25-64-□	25-64-□	25-64-□	25-64-□	25-178-□	25-178-□	25-178-□	25-178-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>130VP</u></b>	<b><u>132VP</u></b>	<b><u>134VP</u></b>	<b><u>136VP</u></b>	<b><u>140VP</u></b>	<b><u>142VP</u></b>	<b><u>144VP</u></b>	<b><u>146VP</u></b>

Notes: (1) Replace '□' with grade required, e.g. 25-64-50C

Housing Model	180VP-1"	180VP-SAE8
Port Size (NPT)	1"	SAE8
Drain Type (NPT)	SAE6	SAE6
Maximum Pressure (psig)	5800	5800
Internal Volume (cc)	750	750
Weight of Housing (lbs)	40.0	40.0
Principle Dimensions: (inches)		
Center Of Port To Head	1.25	1.25
Head Diameter	5.47	5.47
Overall Length	12.79	12.79
Element Removal Clearance	9.06	9.06
Maximum Temp. (250°F) Standard Buna-N O-Ring	BN180VP	BN180VP
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	SL-180-38-172-□	SL-180-38-172-□
<b>Drawing</b> **For More Detail & Options**	<b><u>180VP-1</u></b>	<b><u>180VP-SAE8</u></b>

Housing Model	UHPC5-SL	UHPCSAE12-SL	UHPCSAE16-SL
Port Size	1" NPT	SAE 12	SAE 16
Drain Size	1/4" NPT	SAE 6	SAE 6
Maximum Pressure (psig)	5700	5700	5700
Maximum Temperature (°F)	250	250	250
Internal Volume (cc) (without element)	775	775	775
Weight of Housing (lbs)	26.0	26.0	26.0
Principle Dimensions: (inch)			
Center Of Port To Head	1.16	1.16	1.16
Head Diameter	4.34	4.34	4.34
Overall Length	12.13	12.13	12.13
Element Removal Clearance	9.00	9.00	9.00
Reservoir Depth	1.25	1.25	1.25
Maximum Temp. (250°F) Standard Buna-N O-Ring	BNUHPC	BNUHPC	BNUHPC
Filter Element Codes: (1) Spring Loaded Coalescing Element (Standard) <b>*Other Elements Available-View Drawing</b>	<b><u>SL38-172-□CSX3</u></b>	<b><u>SL38-172-□CSX3</u></b>	<b><u>SL38-172-□CSX3</u></b>
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>UHPC5-SL</u></b>	<b><u>UHPCSAE12-SL</u></b>	<b><u>UHPCSAE16-SL</u></b>

Notes: (1) Replace "□" with grade required, e.g. SL38-172-70CSX3

Housing Model	150	151	152	150-4401	151-4401	152-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1500	1500	1500	1500	1500	1500
Internal Volume (cc)	1350	1350	1350	1350	1350	1350
Weight of Housing (lbs)	22.0	22.0	22.0	22.0	22.0	22.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.18	1.85	1.61	1.18	1.85	1.61
Head Diameter	4.33	4.33	4.57	4.33	4.33	4.57
Overall Length	15.04	15.04	15.83	15.04	15.04	15.83
Element Removal Clearance	9.72	9.72	9.72	9.72	9.72	9.72
Maximum Temp. (400°F) Standard Viton O-Ring	GV150	GV150	GV150	GV150	GV150	GV150
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	51-230-□	51-230-□	51-230-□	SL-51-230-□	SL-51-230-□	SL-51-230-□
<b>Drawing</b> **For More Detail & Options**	<b><u>150</u></b>	<b><u>151</u></b>	<b><u>152</u></b>	<b><u>150-4401</u></b>	<b><u>151-4401</u></b>	<b><u>152-4401</u></b>

Notes: (1) Replace '□' with grade required, e.g. 51-230-50CS

Housing Model	160	161	162	160-4401	161-4401	162-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1500	1500	1500	1500	1500	1500
Internal Volume (cc)	2400	2400	2400	2400	2400	2400
Weight of Housing (lbs)	38.0	38.0	38.0	38.0	38.0	38.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.18	1.85	1.61	1.18	1.85	1.61
Head Diameter	4.33	4.33	4.57	4.33	4.33	4.57
Overall Length	24.49	24.49	25.27	24.49	24.49	25.27
Element Removal Clearance	19.37	19.37	19.37	19.37	19.37	19.37
Maximum Temp. (400°F) Standard Viton O-Ring	GV150	GV150	GV150	GV150	GV150	GV150
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	51-476-□	51-476-□	51-476-□	SL-51-476-□	SL-51-476-□	SL-51-476-□
<b>Drawing</b> **For More Detail & Options**	<b><u>160</u></b>	<b><u>161</u></b>	<b><u>162</u></b>	<b><u>160-4401</u></b>	<b><u>161-4401</u></b>	<b><u>162-4401</u></b>

Notes: (1) Replace '□' with grade required, e.g. 51-476-50CS

Housing Model	150HP	151HP	152HP	150HP-4401	151HP-4401	152HP-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	3000	3000	3000	3000	3000	3000
Internal Volume (cc)	1250	1250	1250	1250	1250	1250
Weight of Housing (lbs)	34.0	34.0	34.0	34.0	34.0	34.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.50	2.05	2.05	1.50	2.05	2.05
Head Diameter	4.72	5.12	5.12	4.72	5.12	5.12
Overall Length	14.29	15.47	15.47	14.29	15.47	15.47
Element Removal Clearance	9.72	9.72	9.72	9.72	9.72	9.72
Maximum Temp. (400°F) Standard Viton O-Ring	GV150HP	GV150HP	GV150HP	GV150HP	GV150HP	GV150HP
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	51-230-□	51-230-□	51-230-□	SL-51-230-□	SL-51-230-□	SL-51-230-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>150HP</u></b>	<b><u>151HP</u></b>	<b><u>152HP</u></b>	<b><u>150HP-4401</u></b>	<b><u>151HP-4401</u></b>	<b><u>152HP-4401</u></b>

Notes: (1) Replace '□' with grade required, e.g. 51-230-50CS

Housing Model	160HP	161HP	162HP	160HP-4401	161HP-4401	162HP-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	3000	3000	3000	3000	3000	3000
Internal Volume (cc)	2500	2500	2500	2500	2500	2500
Weight of Housing (lbs)	57.0	57.0	57.0	57.0	57.0	57.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.50	2.05	2.05	1.50	2.05	2.05
Head Diameter	4.76	5.12	5.12	4.76	5.12	5.12
Overall Length	23.97	25.16	25.16	23.97	25.16	25.16
Element Removal Clearance	19.37	19.37	19.37	19.37	19.37	19.37
Maximum Temp. (400°F) Standard Viton O-Ring	GV160HP/2	GV160HP/2	GV160HP/2	GV160HP/2	GV160HP/2	GV160HP/2
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	51-476-□	51-476-□	51-476-□	SL-51-476-□	SL-51-476-□	SL-51-476-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>160HP</u></b>	<b><u>161HP</u></b>	<b><u>162HP</u></b>	<b><u>160HP-4401</u></b>	<b><u>161HP-4401</u></b>	<b><u>162HP-4401</u></b>

Notes: (1) Replace '□' with grade required, e.g. 51-476-50CS

Housing Model	150VP	151VP	152VP	150VP-4401	151VP-4401	152VP-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	6000	6000	6000	6000	6000	6000
Internal Volume (cc)	1300	1300	1300	1300	1300	1300
Weight of Housing (lbs)	70.0	70.0	70.0	70.0	70.0	70.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.97	1.97	2.16	1.97	1.97	2.16
Head Diameter	5.91	5.91	5.91	5.91	5.91	5.91
Overall Length	17.09	17.09	17.09	17.09	17.09	17.09
Element Removal Clearance	9.72	9.72	9.72	9.72	9.72	9.72
Maximum Temp. (400°F) Standard Viton O-Ring	GV150VP	GV150VP	GV150VP	GV150VP	GV150VP	GV150VP
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	51-230-□	51-230-□	51-230-□	51-230-□	51-230-□	51-230-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>150VP</u></b>	<b><u>151VP</u></b>	<b><u>152VP</u></b>	<b><u>150VP-4401</u></b>	<b><u>151VP</u></b>	<b><u>152VP</u></b>

Notes: (1) Replace '□' with grade required, e.g. 51-230-50CS

Housing Model	160VP	161VP	162VP	160VP-4401	161VP-4401	162VP-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	6000	6000	6000	6000	6000	6000
Internal Volume (cc)	2500	2500	2500	2500	2500	2500
Weight of Housing (lbs)	70.0	70.0	70.0	70.0	70.0	70.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.97	1.97	2.16	1.97	1.97	2.16
Head Diameter	5.91	5.91	5.91	5.91	5.91	5.91
Overall Length	26.58	26.58	26.58	26.58	26.58	26.58
Element Removal Clearance	19.37	19.37	19.37	19.37	19.37	19.37
Maximum Temp. (400°F) Standard Viton O-Ring	GV160VP/2	GV160VP/2	GV160VP/2	GV160VP/2	GV160VP/2	GV160VP/2
Filter Element Codes: (1) Disposable Element (Standard) <b>*Other Elements Available- View Drawing</b>	51-476-□	51-476-□	51-476-□	51-476-□	51-476-□	51-476-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>160VP</u></b>	<b><u>161VP</u></b>	<b><u>162VP</u></b>	<b><u>160VP-4401</u></b>	<b><u>161VP-4401</u></b>	<b><u>162VP-4401</u></b>

Notes: (1) Replace '□' with grade required, e.g. 51-476-50CS