

<b>Housing Model</b>	<b>116IL</b>	<b>126IL</b>	<b>136IL</b>	<b>146IL</b>
Port Size (NPT)	1/4"	1/4"	1/2"	1/2"
Maximum Pressure (psig) (1)	5000	5000	1500	1500
Internal Volume (cc)	15	30	92	220
Weight of Housings (lbs)	1.0	1.0	2.0	3.0
Principle Dimensions: (inches)				
Body Diameter	1.39	1.39	1.89	1.89
Overall Length	3.11	4.09	5.12	9.60
Element Removal Clearance	2.00	3.66	3.67	8.15
Maximum Temp. (400°F) Standard Viton O-Ring	GV126IL-3	GV126IL-3	GV136IL-3	GV136IL-3
Filter Element Codes: (2) Disposable Element (Standard) <b>*Other Elements Available-View Drawing</b>	12-32-□	12-57-□	25-64-□	25-178-□
<b>Drawing</b> <b>**For More Detail &amp; Options**</b>	<b><u>116IL</u></b>	<b><u>126IL</u></b>	<b><u>136IL</u></b>	<b><u>146IL</u></b>

Notes: (1) At 400°F. Above 400°F pressure ratings are reduced – consult UFS for exact rating  
(2) Replace '□' with grade required, e.g. 25-64-50C