

Housing Model	360	365	360F	365F	360A	365A	360AF	365AF
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	Twist	Twist	Automatic	Automatic	Petcock	Petcock	Automatic	Automatic
Maximum Pressure (psig)	150	150	150	150	500	500	250	250
Internal Volume (cc)	148	148	135	135	163	163	150	150
Weight of Housing (lbs)	1.0	1.0	1.0	1.0	1.5	1.5	1.5	1.5
Principle Dimensions: (inches) (1)								
Center of Port to Head	0.61	0.61	0.61	0.61	0.61	0.61	0.61	0.61
Head Diameter	2.72	2.72	2.72	2.72	2.72	2.72	2.72	2.72
Overall Length	6.38	6.38	6.85	6.85	6.26	6.26	6.89	6.89
Element Removal Clearance	3.07	3.07	3.07	3.07	3.07	3.07	3.07	3.07
Maximum Temp. (120°F / 240°F*) Standard Buna-N O-Ring	BN360	BN360	BN360	BN360	BN360	BN360	BN360	BN360
Filter Element Codes: Coalescing Element (Standard - Included) *Other Elements Available- View Drawing	25-64-70C	25-64-70C	25-64-70C	25-64-70C	25-64-70C	25-64-70C	25-64-70C	25-64-70C
Drawing **For More Detail & Options**	<u>360</u>	<u>365</u>	<u>360F</u>	<u>365F</u>	<u>360A</u>	<u>365A</u>	<u>360AF</u>	<u>365AF</u>
No Drain Option **See Drawing For More Detail**	<u>350</u>	<u>355</u>	N/A	N/A	<u>350A</u>	<u>355A</u>	N/A	N/A
Housing Model w/Indicator Max. Pressure with Indicator – 150 PSIG	<u>360I</u>	<u>365I</u>	<u>360FI</u>	<u>365FI</u>	<u>360AI</u>	<u>365AI</u>	<u>360AFI</u>	<u>365AFI</u>

Notes: (1) Dimensions are based on housing and does not include measurement for indicator
(*) Maximum Temperature is 120°F for Polycarbonate and 240°F for Aluminum Bowls

Housing Model	370	375	370F	375F	370A	375A	370AF	375AF
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	Twist	Twist	Automatic	Automatic	Petcock	Petcock	Automatic	Automatic
Maximum Pressure (psig)	150	150	150	150	500	500	250	250
Internal Volume (cc)	290	290	300	300	310	310	300	300
Weight of Housing (lbs)	1.0	1.0	1.0	1.0	1.5	1.5	1.5	1.5
Principle Dimensions: (inches) (1)								
Center Of Port To Head	0.61	0.61	0.61	0.61	0.61	0.61	0.61	0.61
Head Diameter	2.72	2.72	2.72	2.72	2.72	2.72	2.72	2.72
Overall Length	10.32	10.32	10.32	10.32	10.32	10.32	10.32	10.32
Element Removal Clearance	7.21	7.21	5.20	5.20	7.21	7.21	5.20	5.20
Maximum Temp. (120°F / 240°F) (2) Standard Buna-N O-Ring	BN360	BN360	BN360	BN360	BN360	BN360	BN360	BN360
Filter Element Codes: Coalescing Element (Standard-Included) *Other Elements Available- View Drawing	25-178-70C	25-178-70C	25-127-70C	25-127-70C	25-178-70C	25-178-70C	25-127-70C	25-127-70C
Drawing **For More Detail & Options**	<u>370</u>	<u>375</u>	<u>370F</u>	<u>375F</u>	<u>370A</u>	<u>375A</u>	<u>370AF</u>	<u>375AF</u>
Model w/Differential Indicator Maximum Pressure with Indicator–150 PSIG	<u>370I</u>	<u>375I</u>	<u>370FI</u>	<u>375FI</u>	<u>370AI</u>	<u>375AI</u>	<u>370AFI</u>	<u>375AFI</u>

Notes: (1) Dimensions are based on housing and does not include measurement for indicator
(2) Maximum Temperature is 120°F for Polycarbonate and 240°F for Aluminum Bowls