

Housing Model	137	138	147	148
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	150	150	150	150
Internal Volume (cc)	105	105	260	260
Weight of Housing (lbs)	2.5	2.5	3.5	3.5
Principle Dimensions: (inches)				
Center Of Port To Head	0.59	0.59	0.59	0.59
Head Diameter	2.20	2.20	2.20	2.20
Overall Length	5.15	5.15	9.81	9.81
Element Removal Clearance	3.15	3.15	7.56	7.56
Maximum Temp. (400°F) Standard Viton O-Ring	GV137	GV137	GV137	GV137
Filter Element Codes: (1) Disposable Element (Standard) *Other Elements Available-View Drawing	25-64-□	25-64-□	25-178-□	25-178-□
Drawing **For More Detail & Options**	<u>137</u>	<u>138</u>	<u>147</u>	<u>148</u>

Notes: (1) Replace '□' with grade required, e.g. 25-64-50C

Housing Model	117G	127G	137G	138G	147G	148G
Port Size (NPT)	1/4"	1/4"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/8"	1/8"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	100	100	100	100	100	100
Internal Volume (cc)	28	40	105	105	260	260
Weight of Housing (lbs)	1.0	1.0	2.0	2.0	3.0	3.0
Principle Dimensions: (inches)						
Center Of Port To Head	0.47	0.47	0.59	0.59	0.59	0.59
Head Diameter	1.58	1.58	2.20	2.20	2.20	2.20
Overall Length	3.38	4.43	5.15	5.15	9.81	9.81
Element Removal Clearance	1.65	2.64	3.15	3.15	7.56	7.56
Maximum Temp. (400°F) Standard Viton O-Ring	GV127	GV127	GV137	GV137	GV137	GV137
Filter Element Codes: (1) Disposable Element (Standard) *Other Elements Available-View Drawing	12-32-□	12-57-□	25-64-□	25-64-□	25-178-□	25-178-□
Drawing **For More Detail & Options**	<u>117G</u>	<u>127G</u>	<u>137G</u>	<u>138G</u>	<u>147G</u>	<u>148G</u>

Notes: (1) Replace '□' with grade required, e.g. 25-64-50C