

Housing Model	300	305	300A	305A	310	315	310A	315A
Port Size (NPT)	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"
Drain Type (NPT)	No Drain	No Drain	No Drain	No Drain	Twist	Twist	Petcock	Petcock
Maximum Pressure (psig)	150	150	500	500	150	150	500	500
Internal Volume (cc)	40	40	50	50	40	40	50	50
Weight of Housing (lbs)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Principle Dimensions: (inches)								
Center Of Port To Head	0.39	0.39	0.39	0.39	0.39	0.39	0.39	0.39
Head Diameter	1.57	1.57	1.57	1.57	1.57	1.57	1.57	1.57
Overall Length	3.75	3.75	4.06	4.06	4.25	4.25	4.65	4.65
Element Removal Clearance	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50
Maximum Temp. (120°F / 240°F*) Standard Buna-N O-Ring	BN315	BN315	BN315	BN315	BN315	BN315	BN315	BN315
Filter Element Codes: Coalescing Element (Standard-Included) *Other Elements Available- View Drawing	12-32-70C	12-32-70C	12-32-70C	12-32-70C	12-32-70C	12-32-70C	12-32-70C	12-32-70C
Drawing **For More Detail & Options**	<u>300</u>	<u>305</u>	<u>300A</u>	<u>305A</u>	<u>310</u>	<u>315</u>	<u>310A</u>	<u>315A</u>

Notes: (*) Maximum Temperature is 120°F for Polycarbonate and 240°F for Aluminum Bowls
 (●) Primary Filter For Optimal Use

Housing Model	300L	305L	300AL	305AL	310L	315L	310AL	315AL
Port Size (NPT)	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"
Drain Type (NPT)	No Drain	No Drain	No Drain	No Drain	Twist	Twist	Petcock	Petcock
Maximum Pressure (psig)	150	150	500	500	150	150	500	500
Internal Volume (cc)	53	53	45	45	45	45	45	45
Weight of Housing (lbs)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Principle Dimensions: (inches)								
Center Of Port To Head	0.39	0.39	0.39	0.39	0.39	0.39	0.39	0.39
Head Diameter	1.57	1.57	1.57	1.57	1.57	1.57	1.57	1.57
Overall Length	4.41	4.41	4.06	4.06	4.88	4.88	4.65	4.65
Element Removal Clearance	2.01	2.01	2.01	2.01	2.01	2.01	2.01	2.01
Maximum Temp. (120°F / 240°F*) Standard Buna-N O-Ring	BN315	BN315	BN315	BN315	BN315	BN315	BN315	BN315
Filter Element Codes: Coalescing Element (Standard-Included) *Other Elements Available- View Drawing	12-57-70C	12-57-70C	12-57-70C	12-57-70C	12-57-70C	12-57-70C	12-57-70C	12-57-70C
Drawing **For More Detail & Options**	<u>300L</u>	<u>305L</u>	<u>300AL</u>	<u>305AL</u>	<u>310L</u>	<u>315L</u>	<u>310AL</u>	<u>315AL</u>

Notes: (*) Maximum Temperature is 120°F for Polycarbonate and 240°F for Aluminum Bowls
 (●) Primary Filter For Optimal Use