

Housing Model	110	112	114	116	120	122	124	126
Port Size (NPT)	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"
Drain Type (NPT)	1/8"	1/4"	None	None	1/8"	1/4"	None	None
Maximum Pressure (psig)	5000	5000	5000	5000	5000	5000	5000	5000
Internal Volume (cc)	25	25	25	25	34	34	34	34
Weight Of Housing (lbs)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Principle Dimensions: (inches)								
Center Of Port To Head	0.39	0.39	0.39	0.39	0.39	0.39	0.39	0.39
Head Diameter	1.42	1.42	1.42	1.42	1.42	1.42	1.42	1.42
Overall Length	2.92	2.92	2.92	2.92	3.98	3.98	3.98	3.98
Element Removal Clearance	1.57	1.57	1.57	1.57	2.36	2.36	2.36	2.36
Maximum Temp. (400°F) Standard Viton O-Ring	GV110	GV110	GV110	GV110	GV110	GV110	GV110	GV110
Filter Element Codes: (1) Disposable Element (Standard) *Other Elements Available- View Drawing	12-32-□	12-32-□	12-32-□	12-32-□	12-57-□	12-57-□	12-57-□	12-57-□
Drawing **For More Detail & Options**	<u>110</u>	<u>112</u>	<u>114</u>	<u>116</u>	<u>120</u>	<u>122</u>	<u>124</u>	<u>126</u>
Housing w/ PTFE Seals Maximum Temp.-PTFE (400°F) Standard	<u>110S</u>	<u>112S</u>	<u>114S</u>	<u>116S</u>	<u>120S</u>	<u>122S</u>	<u>124S</u>	<u>126S</u>

Notes: (1) Replace '□' with grade required, e.g. 12-32-50C