

Housing Model	310A	315A	360A	365A	370A	375A
Port Size (NPT)	1/8"	1/4"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	Petcock	Petcock	Petcock	Petcock	Petcock	Petcock
Maximum Pressure (psig)	500	500	500	500	500	500
Internal Volume (cc)	45	45	163	163	310	310
Weight of Housing (lbs)	0.5	0.5	1.5	1.5	1.5	1.5
Principle Dimensions: (inches)						
Center Of Port To Head	0.39	0.39	0.61	0.61	0.61	0.61
Head Diameter	1.57	1.57	2.72	2.72	2.72	2.72
Overall Length	4.65	4.65	6.26	6.26	10.32	10.32
Element Removal Clearance	1.50	1.50	3.07	3.07	7.21	7.21
Maximum Temp. (240°F) Standard Viton O-Ring	BN315	BN315	BN360	BN360	BN360	BN360
Filter Element Codes: Coalescing Element (Standard - Included)	12-32-70C	12-32-70C	25-64-70C	25-64-70C	25-178-70C	25-178-70C
*Other Elements Available- View Drawing						
Drawing **For More Detail & Options**	<u>310A</u>	<u>315A</u>	<u>360A</u>	<u>365A</u>	<u>370A</u>	<u>375A</u>

Housing Model	380AHP	383AHP	385AHP	390AHP
Port Size (NPT)	3/4"	1"	1 1/2" or 2"	2"
Drain Type (NPT)	Petcock	Petcock	Petcock	Petcock
Maximum Pressure (psig)	1,500	1,500	1,000	1,000
Internal Volume (cc)	760	760	1500	2950
Weight of Housing (lbs)	8	8	11	14
Principle Dimensions: (inches)				
Center Of Port To Head	1.34	1.34	1.58	1.58
Head Diameter	4.33	4.33	5.51	5.51
Overall Length	12.09	12.09	15.67	25.39
Element Removal Clearance	6.19	6.19	9.30	18.98
Maximum Temp. (250°F) Standard Viton O-Ring	BN380	BN380	BN385	BN385
Filter Element Codes: Coalescing Element (Standard - Included)	TRE38-152-70CS	TRE38-152-70CS	51-230-70CS	51-476-70CS
*Other Elements Available- View Drawing				
Drawing **For More Detail & Options**	<u>380AHP</u>	<u>383AHP</u>	<u>385AHP</u>	<u>390AHP</u>