

Housing Model	130	132	134	136	140	142	144	146
Port Size (NPT)	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"	1/4"	1/2"
Drain Type (NPT)	1/4"	1/4"	None	None	1/4"	1/4"	None	None
Maximum Pressure (psig)	1500	1500	1500	1500	1500	1500	1500	1500
Internal Volume (cc)	100	100	100	100	260	260	260	260
Weight of Housing (lbs)	2.5	2.5	2.5	2.5	3.5	3.5	3.5	3.5
Principle Dimensions: (inches)								
Center Of Port To Head	0.59	0.59	0.59	0.59	0.59	0.59	0.59	0.59
Head Diameter	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36
Overall Length	4.80	4.80	4.80	4.80	9.33	9.33	9.33	9.33
Element Removal Clearance	2.95	2.95	2.95	2.95	7.40	7.40	7.40	7.40
Maximum Temp. (400°F) Standard Viton O-Ring	GV130	GV130	GV130	GV130	GV130	GV130	GV130	GV130
Filter Element Codes: (1) Disposable Element (Standard) *Other Elements Available- View Drawing	25-64-□	25-64-□	25-64-□	25-64-□	25-178-□	25-178-□	25-178-□	25-178-□
Drawing **For More Detail & Options**	<u>130</u>	<u>132</u>	<u>134</u>	<u>136</u>	<u>140</u>	<u>142</u>	<u>144</u>	<u>146</u>
Housing w/ PTFE Seals Maximum Temp. -PTFE (400°F) Standard	<u>130S</u>	<u>132S</u>	<u>134S</u>	<u>136S</u>	<u>140S</u>	<u>142S</u>	<u>144S</u>	<u>146S</u>

Notes: (1) Replace '□' with grade required, e.g. 25-64-50C