

Housing Model	150	151	152	150-4401	151-4401	152-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1500	1500	1500	1500	1500	1500
Internal Volume (cc)	1350	1350	1350	1350	1350	1350
Weight of Housing (lbs)	22.0	22.0	22.0	22.0	22.0	22.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.18	1.85	1.61	1.18	1.85	1.61
Head Diameter	4.33	4.33	4.57	4.33	4.33	4.57
Overall Length	15.04	15.04	15.83	15.04	15.04	15.83
Element Removal Clearance	9.72	9.72	9.72	9.72	9.72	9.72
Maximum Temp. (400°F) Standard Viton O-Ring	GV150	GV150	GV150	GV150	GV150	GV150
Filter Element Codes: (1) Disposable Element (Standard) *Other Elements Available- View Drawing	51-230-□	51-230-□	51-230-□	SL-51-230-□	SL-51-230-□	SL-51-230-□
Drawing **For More Detail & Options**	<u>150</u>	<u>151</u>	<u>152</u>	<u>150-4401</u>	<u>151-4401</u>	<u>152-4401</u>

Notes: (1) Replace '□' with grade required, e.g. 51-230-50CS

Housing Model	160	161	162	160-4401	161-4401	162-4401
Port Size (NPT)	1"	1 1/2"	2"	1"	1 1/2"	2"
Drain Type (NPT)	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	1500	1500	1500	1500	1500	1500
Internal Volume (cc)	2400	2400	2400	2400	2400	2400
Weight of Housing (lbs)	38.0	38.0	38.0	38.0	38.0	38.0
Principle Dimensions: (inches)						
Center Of Port To Head	1.18	1.85	1.61	1.18	1.85	1.61
Head Diameter	4.33	4.33	4.57	4.33	4.33	4.57
Overall Length	24.49	24.49	25.27	24.49	24.49	25.27
Element Removal Clearance	19.37	19.37	19.37	19.37	19.37	19.37
Maximum Temp. (400°F) Standard Viton O-Ring	GV150	GV150	GV150	GV150	GV150	GV150
Filter Element Codes: (1) Disposable Element (Standard) *Other Elements Available- View Drawing	51-476-□	51-476-□	51-476-□	SL-51-476-□	SL-51-476-□	SL-51-476-□
Drawing **For More Detail & Options**	<u>160</u>	<u>161</u>	<u>162</u>	<u>160-4401</u>	<u>161-4401</u>	<u>162-4401</u>

Notes: (1) Replace '□' with grade required, e.g. 51-476-50CS