



Aluminum End of Line Filters

Features

- Ideal Room - Air Monitor Filters
- Keep Sample Lines Clean
- Choice of Sizes - 1/8", 1/4" or 1/2"
- Custom Units Available
- Easy to Replace Filter Element

Applications

- Protect Air Intake Analyzers
- Can Be Utilized as Vacuum Exhaust Filter
- Ambient Gas Storage Farm Filter
- Remote Monitor / Sensor Protection

Our End of the Line Filters are specifically designed for use in environmental monitoring systems. They accept disposable microfiber, SS, PTFE and our PEL filter elements for particulate removal at the sampling point, thereby keeping sample lines and control systems clean. Our Disposable In-Line Filters (DIF) are also ideal for this type of application.



Housing Model	910	910E	915	915E	920	920E
Connection Size	1/4" O.D. tubing	1/8" NPT	1/4" O.D. tubing	1/4" NPT	1/4" O.D. tubing	1/2" NPT
Maximum Pressure (psig)	30	30	30	30	30	30
Maximum Temperature (°F)	300	300	300	300	300	300
Principle Dimensions: (inches)						
Body Diameter	0.75	1.42	1.42	1.42	1.42	1.97
Overall Length	1.97	1.97	2.95	3.08	3.56	3.64
Filter Element Codes:						
Coalescing Element (Standard)	12-32-□	12-32-□	12-57-□	12-57-□	25-64-□	25-64-□
Other Elements Available – View Drawing						

Drawing
****For More Detail & Options**** **910** **910E** **915** **915E** **920** **920E**

Notes: (1) Replace '□' with grade or micron required, e.g. 25-64-50C, PT-25-64-03

Element Sold Separately

