



Onstream Liquid Filter Housings

Features

- One-Piece Bowl for Quick & Spill Free Element Service
- Extra Bottom Reservoir Capacity for Sediment Deposit Collection
- Wide Variety of Filter Elements Available
- 250 PSIG Maximum, 1/2", 3/4" and 1" NPT Port Sizes
- Accepts Industry Standard Elements

Applications

- Food Processing
- Corrosive Liquid Service
- Batch Service Filtration
- Heavy Duty Service

Our Onstream Filter Housings are ideal for a variety of liquid purification solutions. Port sizes available are 1/2", 3/4" or 1" NPT.

Choose from a variety of off the shelf, disposable or re-cleanable DOE cartridges. Our disposable elements include spun polypropylene and pleated cartridges. We also offer a wide range of re-cleanable pleated stainless steel cartridges from 5 micron up to 500 micron.

An extensive range of elements can be used for coolant, process water, paint, or petro-chemical applications. Our selection affords accurate solutions based upon the contaminants to be removed, the level of filtration, and the relative importance of cost, and element life.



Housing Model	SLH818	SLH820	SLH895
Port Size (NPT) Specify Size	1/2", 3/4" or 1"	1/2", 3/4" or 1"	1/2", 3/4" or 1"
Drain Type (NPT)	1/8"	1/8"	1/8"
Maximum Pressure (psig)	250	250	250
Principle Dimensions: (inches)			
Head Diameter	4.00	4.00	4.00
Overall Length	8.875	13.75	23.875
Cartridge Length	4.875	9.875	19.875
Element Removal Clearance	1.50	1.50	1.50
Maximum Temp. (400°F) Standard Viton O-Ring	GVSLH	GVSLH	GVSLH
Filter Element Codes (1): Spun Polypropylene Element (Standard) **Other Elements Available-View Drawing**	LE-818-P□	LE-820-P□	LE-895-P□
Drawing **For More Detail & Options**	<u>SLH818</u>	<u>SLH820</u>	<u>SLH895</u>

Notes: (1) Replace the '□' with micron required

