



Features

- Caged Pyrex Bowl for Safety
- One Tie Rod Makes Service Quick & Simple

Applications

- Level Indicator
- Flow Indicator
- Four Standard Sizes

We offer four standard sizes of sight glass housings which are based upon our Pyrex / SS filter assemblies. These units provide a caged Pyrex bowl to monitor tank or boiler liquid levels safely. The compact model SG117 is especially suited as a flow monitor. All the units utilize a double open-ended glass bowl which is "sandwiched" between two stainless steel end plates. Our design eliminates the cumbersome external bolts which is normal on many other brands. We feel our design simplifies installation and service.



Housing Model	SG117	SG127	SG137	SG147
Port Size (NPT)	1/4"	1/4"	1/4"	1/4"
Maximum Pressure (psig)	100	100	100	100
Internal Volume (cc)	26	36	105	255
Principle Dimensions: (inches)				
Head Diameter	1.57	1.57	2.20	2.20
Overall Length	3.07	3.82	4.65	9.13
Removal Clearance	2.46	2.76	3.54	8.03
Maximum Temp. (400°F)				
Standard Viton O-Ring	GVSG117	GVSG127	GVSG137	GVSG137
Drawing	SG117	SG127	SG137	SG147
For More Detail & Options				

