



# SS Differential Pressure Gauge

## Features

- 1500 PSIG Working Pressure
- Stainless Steel Body & End Cap
- Stainless Steel Piston Design
- Accuracy  $\pm 5\%$  F.S. Ascending
- Range: 0-7 PSIG, 7-11 PSIG, to 11-15 PSIG

## Applications

- Filter Monitoring
- Automatically Resets Upon Element Service
- Remote Monitoring
- Flexibility for Gas & Liquid Filtration
- For Particulate or Coalescing Service

The SS150VDI process visual indicator is designed to be factory installed on our 1500 PSIG model 150-160 series of filter housings. The piston magnet design and stainless steel wetted construction allows this "filter Minder" to be utilized in a vast range of gases and liquids. The dual sided, tri-colored gauge is easy to read and provides accurate information to the operator regarding filter life.



## SPECIFICATIONS ON THE SS150VDI

Differential Pressure Range 0-5 PSID to 0-15 PSID  
Accuracy  $\pm 5\%$  Full Scale Ascending  
Dual Dial – Size 1 1/4" x 2 1/4" Oval  
Working Pressure 1,500 PSIG  
Operating Temperature: -40°F to +200°F  
316L Stainless Steel Body  
Viton O-Rings  
Polycarbonate Gauge Cover

Dimensions: 1.25"H x 1.62"W x 2.48"L  
Weight: 1 lb.

Must Be Factory Installed

